



ILLINOIS DEPARTMENT OF NATURAL RESOURCES

Office of Oil and Gas

Division of Oil and Gas

One Natural Resources Way
Springfield, Illinois 62702-1271
(217) 782-7756



OG-22B FIELD PLUGGING INSTRUCTIONS

PERMITTEE:
PERMITTEE #: REF. #: PERMIT:
WELL NAME:
LOCATION:
WELL TYPE: COUNTY:
SEC.: TWP.: RANGE:

BOTTOM HOLE AND PRODUCING/INJECTION INTERVAL PLUGS:

Cement shall be placed opposite any formation encountered in well which is or has been produced or into which injection is occurring, within one-fourth (1/4) mile radius of well bore. For each formation encountered, cement shall be placed from T.D. or fifty (50) feet below formation (whichever is less) to fifty (50) feet above producing or injection formation.

COAL PLUG:

Start cement plug at feet and cement to feet.

FRESHWATER PLUG:

- 1. Base of freshwater or bottom of surface casing:
2. Start cement plug at feet and cement to surface.
A. Top of freshwater plug after laying down drill string.
B. Cement rathole from T.D. to surface.

IF PLUGGED BEFORE 8:00 AM OR AFTER 4:00 PM, THE FOLLOWING IS REQUIRED:

- 1. Call District Office before plugging begins and leave a message with well name, Permittee name and approximate time plugging will begin.
2. Retain a copy of the cement records indicating the number of sacks of cement and depths of cement plugs.
3. Call the District Office the next business day to set up an appointment to fill out an OG-6 (Plugging Report Form) and turn in a copy of cement records.

Inspector

Date of visit